


Beckett**UltraGuard™**

A product of International Lubrication and Fuel Consultants

**Dosage
Chart****Normal Preventative Maintenance**

<i>Fuel Gallons</i>	<i>Additive Ounces</i>	<i>Fuel Gallons</i>	<i>Additive Ounces</i>
100	1	3750	32 (1 quart)
200	1.5	4000	34
250	2	4250	36
500	4	4500	38
750	6	4750	40
1000	8	5000	42
1250	10	5500	46
1500	13	6000	50
1750	16 (1 pint)	6500	56
2000	18 (1 pint + 2 oz)	7000	60
2250	19 (1 pint + 3 oz)	7500	64 (1/2 gallon)
2500	21	8000	68
2750	24	8500	74
3000	26	9000	78
3250	28	9500	82
3500	30	10,000	86

Note: For tanks with known sludge build-up, see higher "Treatment" dosage on reverse side.

Special Heavy Duty Treatment

<i>Fuel Gallons</i>	<i>Additive Ounces</i>	<i>Fuel Gallons</i>	<i>Additive Ounces</i>
100	2	3750	64 (1/2 gallon)
200	3	4000	68
250	4	4250	72
500	8	4500	76
750	12	4750	80
1000	16 (1 pint)	5000	84
1250	20	5500	92
1500	26	6000	100
1750	30	6500	112
2000	34 (1 quart + 2 oz)	7000	120
2250	38	7500	128 (1 gallon)
2500	42	8000	136
2750	48	8500	148
3000	52	9000	156
3250	56	9500	164
3500	60	10,000	172

Courtesy of International Lubrication and Fuel Consultants, Inc.



Beckett
ADDITIVES

Beckett Additives LLC

Mailing Address: P.O. Box 1928 • Elyria, OH 44036

Shipping Address: 38251 Center Ridge Road • North Ridgeville, OH 44039

Phone: 440-353-6330 • 866-OIL-CURE (866-645-2873)

Web: www.beckettadditives.com

UltraGuard™ is a registered trademark of Fuel Management Services of Jeffersonson, VA.

© 2004 Beckett Additives LLC

Printed in U.S.A.
BA0004 R7/04